

BEST AVAILABLE COPY

Amendment to the Claims

1. (currently amended) A process for a simplified access control language that controls
5 access to directory entries in a computer environment, comprising the steps of:

~~providing a system administrator defined creating a read access control list (ACL)~~
command for a user[(:)], wherein said

~~said system administrator defined read access control list~~ listing lists a set
of Lightweight Directory Access Protocol (LDAP) user attributes ~~that are selected created~~
10 and controlled by said administrator;

said user applying said read access control list command by listing selecting a
subset from said system administrator defined LDAP user attributes for allowing authorizing
user-defined read access to said subset of user attributes to one or more other users[(:)],
and by listing

15 ~~providing a user defined access control command attribute read list containing user~~
identifications of said one or more other users such that said one or more other users that are
allowed authorized to have read access to said user-defined subset of said system
administrator defined LDAP user attributes; and

20 ~~storing said read access control list command in a directory, said directory containing~~
said user attributes; and

~~responsive to one or more other users accessing any of said user attributes in said~~
directory, said read access control list command referring to said user-defined read list of
user identifications at runtime thereby allowing said read user identifications one or more
other users read access to said system administrator defined LDAP user attributes[(:)]

25 ~~wherein said read access control command resides in a directory containing said LDAP~~
attributes.

2. (original) The process of Claim 1, wherein upon a client read access, the directory server
selects a specific read access control command according to the attribute being accessed
30 and refers to the read list of the owner of the attribute being accessed to determine if said
client has permission to execute said read access.

3. (original) The process of Claim 1, further comprising the steps of:

35 providing a user defined write list containing user identifications that are allowed to
write a specified set of attributes;

providing a system administrator defined write access control command;

said write access control command listing the user attributes that said administrator has selected for user defined write access; and

said write access control command referring to said user defined write list thereby allowing said write user identifications write access to said user attributes.

5

~~4. (original) The process of Claim 3, wherein upon a client write access, the directory server selects a specific write access control command according to the attribute being accessed and refers to the write list of the owner of the attribute being accessed to determine if said client has permission to execute said write access.~~

10

5. (currently amended) A process for a simplified access control language that controls access to directory entries in a computer environment, comprising the steps of:

~~providing for a user a system administrator creating a defined read access control list (ACL) command that lists Lightweight Directory Access Protocol (LDAP) user attributes that~~
15 ~~said administrator has selected created~~ for user defined read access, said user selecting a subset of user-defined said LDAP user attributes from said list for read access to one or more other users;

~~providing for a user a system administrator creating a defined write access control list (ACL) command that lists Lightweight Directory Access Protocol (LDAP) user attributes that~~
20 ~~said administrator has selected created~~ for user defined write access, said user selecting a subset of user-defined said LDAP user attributes from said list for write access to one or more other users;

providing a plurality of user defined access control list command attribute read lists containing user identifications of said one or more other users that are allowed to read said
25 user defined subset from said LDAP user attributes that said administrator has selected created for user defined read access; and

providing a plurality of user defined access control list command attribute write lists containing user identifications of said one or more other users that are allowed to write said
30 user defined subset from said LDAP user attributes that said administrator has selected created for user defined write access; and

wherein storing said read access control list command and said write access control list command reside in a directory containing said LDAP user attributes;

wherein when a client responsive to one or more other users requesting read access to one of the LDAP user attributes ~~that said administrator has selected for user defined read~~
35 ~~access occurs, applying~~ said read access control list command and the read list of the owner

of the attribute being accessed ~~are used to determine if said client one or more other users~~
has permission to execute said read access; and

wherein ~~when a client responsive to one or more other users requesting write access~~
to one of the LDAP user attributes that ~~said administrator has selected for user defined write~~
5 ~~access occurs, applying said write access control list command and the write list of the owner~~
~~of the attribute being accessed are used to determine if said client one or more other users~~
has permission to execute said write access.

6. (currently amended) A process for a simplified access control language that controls
10 access to directory entries in a computer environment, comprising the steps of:

~~providing a system administrator defined creating a write access control list (ACL)~~
command for a user[(:)], wherein said

~~said system administrator defined write access control list command listing lists a set~~
of Lightweight Directory Access Protocol (LDAP) user attributes ~~that are selected created~~
15 and controlled by said administrator;

~~said user applying said write access control list command by listing selecting a~~
subset from said system administrator defined LDAP user attributes for ~~allowing authorizing~~
~~user defined write access to said subset of user attributes to one or more other users[(:)],~~
and by listing

20 ~~providing a user defined access control command attribute write list containing user~~
~~identifications of said one or more other users such that said one or more other users that are~~
allowed ~~authorized~~ to have write access to said user defined subset of said system
administrator defined LDAP user attributes; and

~~storing said write access control list command in a directory, said directory containing~~
25 ~~said user attributes; and~~

~~responsive to one or more other users accessing any of said user attributes in said~~
directory, said write access control list command referring to said ~~user defined write list of~~
~~user identifications~~ at runtime thereby allowing said ~~write user identifications one or more~~
~~other users~~ write access to said system administrator defined LDAP user attributes[(:)]

30 ~~wherein said write access control command resides in a directory containing said LDAP~~
attributes.

7. (original) The process of Claim 6, wherein upon a client write access, the directory server
selects a specific write access control command according to the attribute being accessed
35 and refers to the write list of the owner of the attribute being accessed to determine if said
client has permission to execute said write access.

8. (original) The process of Claim 6, further comprising the steps of:
providing a user defined read list containing user identifications that are allowed to
read a specified set of attributes; and

5 providing a system administrator defined read access control command;

~~wherein said read access control command lists the user attributes that said~~
administrator has selected for user defined read access; and
wherein said read access control command refers to said user defined read list thereby
allowing said read user identifications read access to said user attributes.

10

9. (original) The process of Claim 8, wherein upon a client read access, the directory server
selects a specific read access control command according to the attribute being accessed
and refers to the read list of the owner of the attribute being accessed to determine if said
client has permission to execute said read access.

15

10. (currently amended) An apparatus for a simplified access control language that controls
access to directory entries in a computer environment, comprising:

means for a system administrator defined creating a read access control list (ACL)
command for a user[(:)]; wherein said

20

means for said system administrator defined read access control list command listing
lists a set of Lightweight Directory Access Protocol (LDAP) user attributes that are selected
created and controlled by said administrator;

means for said user applying said read access control list command by listing
selecting a subset from said system administrator defined LDAP user attributes for allowing
25 authorizing user defined read access to said subset of user attributes to one or more other
users[(:)]; and by listing

25

a user defined access control command attribute read list containing user
identifications of said one or more other users such that said one or more other users that are
allowed authorized to have read access to said user defined subset of said system
30 administrator defined LDAP user attributes; and

30

means for storing said read access control list command in a directory, said directory
containing said user attributes; and

responsive to one or more other users accessing any of said user attributes in said
directory, means for said read access control list command referring to said user defined
35 read list of user identifications at runtime thereby allowing said read user identifications one or
more other users read access to said system administrator defined LDAP user attributes[(:)]

35

~~wherein said read access control command resides in a directory containing said LDAP user attributes.~~

11.(original) The apparatus of Claim 10, wherein upon a client read access, the directory
5 server selects a specific read access control command according to the attribute being
~~accessed and refers to the read list of the owner of the attribute being accessed to~~
determine if said client has permission to execute said read access.

12.(original) The apparatus of Claim 10, further comprising:

10 a user defined write list containing user identifications that are allowed to write a
specified set of attributes; and

a system administrator defined write access control command;

wherein said write access control command lists the user attributes that said
administrator has selected for user defined write access; and

15 wherein said write access control command refers to said user defined write list
thereby allowing said write user identifications write access to said user attributes.

13.(original) The apparatus of Claim 12, wherein upon a client write access, the directory
server selects a specific write access control command according to the attribute being
20 accessed and refers to the write list of the owner of the attribute being accessed to
determine if said client has permission to execute said write access.

14.(currently amended) An apparatus for a simplified access control language that controls
access to directory entries in a computer environment, comprising:

25 means for a system administrator creating a defined read access control list (ACL)
command for a user that lists Lightweight Directory Access Protocol (LDAP) user attributes
that said administrator has ~~selected~~ created for user defined read access, said user selecting
a subset of user-defined said LDAP user attributes from said list for read access to one or
more other users;

30 means for a system administrator creating a defined write access control list (ACL)
command for a user that lists LDAP user attributes that said administrator has ~~selected~~
created for user defined write access, said user selecting a subset of user-defined said
LDAP user attributes from said list for write access to one or more other users;

a plurality of user defined access control list command attribute read lists containing
35 user identifications of said one or more other users that are allowed to read said user defined

subset from said LDAP user attributes that said administrator has ~~selected~~ created for user defined read access; and

a plurality of user defined access control list command attribute write lists containing user identifications of said one or more other users that are allowed to write said user defined subset from said LDAP user attributes that said administrator has ~~selected~~ created for user defined write access, and

~~wherein storing~~ said read access control list command and said write access control list command reside in a directory containing said LDAP user attributes;

~~wherein when a client responsive to one or more other users requesting~~ read access to one of the LDAP user attributes that said administrator has ~~selected for user defined read access occurs~~, applying said read access control list command and the read list of the owner of the attribute being accessed are used to determine if said client one or more other users has permission to execute said read access; and

~~wherein when a client responsive to one or more other users requesting~~ write access to one of the LDAP user attributes that said administrator has ~~selected for user defined write access occurs~~, applying said write access control list command and the write list of the owner of the attribute being accessed are used to determine if said client one or more other users has permission to execute said write access.

15. (currently amended) An apparatus for a simplified access control language that controls access to directory entries in a computer environment, comprising:

means for a system administrator defined creating a write access control list (ACL) command for a user[(:)], wherein said

means for said system administrator defined write access control list command listing lists a set of Lightweight Directory Access Protocol (LDAP) user attributes that are selected created and controlled by said administrator;

means for said user applying said write access control list command by listing selecting a subset from said system administrator defined LDAP user attributes for allowing authorizing user defined write access to said subset of user attributes to one or more other users[(:)], and by listing

a user defined access control command attribute write list containing user identifications of said one or more other users such that said one or more other users that are allowed authorized to have write access to said user defined subset of said system administrator defined LDAP user attributes; and

means for storing said write access control list command in a directory, said directory containing said user attributes; and

responsive to one or more other users accessing any of said user attributes in said directory, means for said write access control list command referring to said user-defined write list of user identifications at runtime thereby allowing said write-user identifications one or more other users write access to said system administrator defined LDAP user attributes[;:]

~~wherein said write access control command resides in a directory containing said LDAP user attributes.~~

16.(original) The apparatus of Claim 15, wherein upon a client write access, the directory server selects a specific write access control command according to the attribute being accessed and refers to the write list of the owner of the attribute being accessed to determine if said client has permission to execute said write access.

17.(original) The apparatus of Claim 15, further comprising:

a user defined read list containing user identifications that are allowed to read a specified set of attributes;

a system administrator defined read access control command;

wherein said read access control command lists the user attributes that said administrator has selected for user defined read access; and

wherein said read access control command refers to said user defined read list thereby allowing said read user identifications read access to said user attributes.

18.(original) The apparatus of Claim 17, wherein upon a client read access, the directory server selects a specific read access control command according to the attribute being accessed and refers to the read list of the owner of the attribute being accessed to determine if said client has permission to execute said read access.

19.(currently amended) A program storage medium readable by a computer, tangibly embodying a program of instructions executable by the computer to perform method steps for a simplified access control language that controls access to directory entries in a computer environment, comprising the steps of:

providing a system administrator defined creating a read access control list (ACL) command for a user[;:], wherein said

~~said system administrator defined read access control list~~ command listing lists a set of Lightweight Directory Access Protocol (LDAP) user attributes that are selected created and controlled by said administrator;

said user applying said read access control list command by listing selecting a subset from said system administrator defined LDAP user attributes for allowing authorizing user-defined read access to said subset of user attributes to one or more other users[;]], and by listing

5 providing a user-defined access control command attribute read list containing user identifications of said one or more other users such that said one or more other users that are
allowed authorized to have read access to said user-defined subset of said system administrator defined LDAP user attributes; and

10 storing said read access control list command in a directory, said directory containing said user attributes; and

responsive to one or more other users accessing any of said user attributes in said directory, said read access control list command referring to said user-defined read list of user identifications at runtime thereby allowing said read-user identifications one or more other users read access to said system administrator defined LDAP user attributes[;]]

15 wherein said read access control command resides in a directory containing said LDAP attributes.

20. (original) The method of Claim 19, wherein upon a client read access, the directory server selects a specific read access control command according to the attribute being
20 accessed and refers to the read list of the owner of the attribute being accessed to determine if said client has permission to execute said read access.

21. (original) The method of Claim 19, further comprising the steps of:

25 providing a user defined write list containing user identifications that are allowed to write a specified set of attributes;

providing a system administrator defined write access control command;

said write access control command listing the user attributes that said administrator has selected for user defined write access; and

30 said write access control command referring to said user defined write list thereby allowing said write user identifications write access to said user attributes.

22. (original) The method of Claim 21, wherein upon a client write access, the directory server selects a specific write access control command according to the attribute being
35 accessed and refers to the write list of the owner of the attribute being accessed to determine if said client has permission to execute said write access.

23.(currently amended) A program storage medium readable by a computer, tangibly embodying a program of instructions executable by the computer to perform method steps for a simplified access control language that controls access to directory entries in a computer environment, comprising the steps of:

5 ~~providing for a user a system administrator creating a defined read access control list (ACL) command that lists Lightweight Directory Access Protocol (LDAP) user attributes that said administrator has selected~~ created for user defined read access, said user selecting a subset of ~~user-defined~~ said LDAP user attributes from said list for read access to one or more other users;

10 ~~providing for a user a system administrator creating a defined write access control list (ACL) command that lists Lightweight Directory Access Protocol (LDAP) user attributes that said administrator has selected~~ created for user defined write access, said user selecting a subset of ~~user-defined~~ said LDAP user attributes from said list for write access to one or more other users;

15 providing a plurality of user defined access control list command attribute read lists containing user identifications of said one or more other users that are allowed to read said user defined subset from said LDAP user attributes that said administrator has ~~selected~~ created for user defined read access; and

20 providing a plurality of user defined access control list command attribute write lists containing user identifications of said one or more other users that are allowed to write said user defined subset from said LDAP user attributes that said administrator has ~~selected~~ created for user defined write access; and

 wherein ~~storing~~ said read access control list command and said write access control list command reside in a directory containing said LDAP user attributes;

25 wherein ~~when a client responsive to one or more other users requesting read access to one of the LDAP user attributes that said administrator has selected for user-defined read access occurs,~~ applying said read access control list command and the read list of the owner of the attribute being accessed ~~are used to determine if said client~~ one or more other users has permission to execute said read access; and

30 wherein ~~when a client responsive to one or more other users requesting write access to one of the LDAP user attributes that said administrator has selected for user-defined write access occurs,~~ applying said write access control list command and the write list of the owner of the attribute being accessed ~~are used to determine if said client~~ one or more other users has permission to execute said write access.

35

24.(currently amended) A program storage medium readable by a computer, tangibly embodying a program of instructions executable by the computer to perform method steps for a simplified access control language that controls access to directory entries in a computer environment, comprising the steps of:

5 ~~providing a system administrator defined creating a write access control list (ACL)~~
~~command for a user[(:)], wherein said~~

~~said system administrator defined write access control list command listing lists a set of Lightweight Directory Access Protocol (LDAP) user attributes that are selected created and controlled by said administrator;~~

10 ~~said user applying said write access control list command by listing selecting a subset from said system administrator defined LDAP user attributes for allowing authorizing user-defined write access to said subset of user attributes to one or more other users[(:)], and by listing~~

15 ~~providing a user-defined access control command attribute write list containing user identifications of said one or more other users such that said one or more other users that are allowed authorized to have write access to said user-defined subset of said system administrator defined LDAP user attributes; and~~

~~storing said write access control list command in a directory, said directory containing said user attributes; and~~

20 ~~responsive to one or more other users accessing any of said user attributes in said directory, said write access control list command referring to said user-defined write list of user identifications at runtime thereby allowing said write-user identifications one or more other users write access to said system administrator defined LDAP user attributes[(:)]~~

25 ~~wherein said write access control command resides in a directory containing said LDAP attributes.~~

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.